

**1/2" Flexible (LDF4-50A) 7/16 DIN Female to 4.3-10 Male Low PIM Jumper | 123-1DFHM**
|123e.com

Part Number: 123-1DFHM-XX-P

7/16 DIN Female to 4.3-10 Male Low PIM factory made jumper. 123eWireless factory made assemblies are optimized to produce low passive third order inter-modulation. Each jumper is dynamically PIM tested to IEC 62037 standards, certified to guarantee performance and averages -165dBc. MADE in the USA. The cable is equivalent to Commscope LDF4-50, and RFS LCF12-50J-P7.

CROSS REFERENCE

Alternative To	L4A-PHMDF, L4-HMDF-6-D
----------------	------------------------

PHYSICAL SPECIFICATIONS

Connector A	7/16 DIN Female
Connector B	4.3-10 Male
Outer Diameter	.63in
Jacket Color	Black
Jacket Material	PE - UV Resistant
Maximum Bending Radius	2.00"

ELECTRICAL SPECIFICATIONS

Frequency Range	600-3000 Mhz
Impedance	50 Ohm
PIM	-165 dBc IEC 62037
Return Loss	-30 db

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-40°C to +85°C
Weather Standard	IEC 68 40/85/ 21

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.