



1/4" Super Flex 7/16" Male to NEX10 Male w/EasyBoot, Low PIM jumper |
123-14SFDMXM-XX-P-EB2 |123e.com
Part Number: 123-14SFDMXM-XX-P-EB2

7/16" DIN Male to NEX10™ Male welded onto 1/4 inch Super Flexible jumper cable MADE IN THE USA. The NEX10™ connector has the EasyBoot weather proofing system to weather proof your connectors when mated. This small cell or DAS jumper is designed with few internal components which in turn reduces the inter-modulation distortion (IMD) averaging -165dBc. Each jumper is individually tested and certified to guarantee performance.

CROSS REFERENCE

Alternative To

PHYSICAL SPECIFICATIONS

Connector A	7/16" DIN Male
Connector B	Nex10 Male with EasyBoot
Outer Diameter	0.252in
Jacket Color	Black
Jacket Material	PE - UV Resistant
Maximum Bending Radius	0.78"

ELECTRICAL SPECIFICATIONS

Frequency Range	600-3000 Mhz
Impedance	50 Ohm
PIM	-168 dBc
Return Loss	≤-27dB @3GHz, ≤-24dB @6GHz

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-40°C to +85°C
Weather Standard	IEC 68 40/85/ 21