



**1/4" Super Flex 7/16" Male to 7/16" Male Right Angle Low PIM jumper | 123-14SFDMDMR | 123e.com**

Part Number: 123-14SFDMDMR-XX-P

1/4" Super Flex 7/16" Male to 7/16" Male Right Angle welded onto 1/4 inch Super Flexible jumper cable MADE IN THE USA. This small cell or DAS jumper is designed with few internal components which in turn reduces the inter-modulation distortion (IMD) averaging -165dBc. Each jumper is individually tested and certified to guarantee performance.

#### CROSS REFERENCE

|                |                          |
|----------------|--------------------------|
| Alternative To | F1A-DMHM, F1A-DMDMR-20-P |
|----------------|--------------------------|

#### PHYSICAL SPECIFICATIONS

|                        |                            |
|------------------------|----------------------------|
| Connector A            | 7/16" DIN Male             |
| Connector B            | 7/16" DIN Male Right Angle |
| Outer Diameter         | 0.252in                    |
| Jacket Color           | Black                      |
| Jacket Material        | PE - UV Resistant          |
| Maximum Bending Radius | 0.78"                      |

#### ELECTRICAL SPECIFICATIONS

|                 |                            |
|-----------------|----------------------------|
| Frequency Range | 600-3000 Mhz               |
| Impedance       | 50 Ohm                     |
| PIM             | -168 dBc                   |
| Return Loss     | ≤-27dB @3GHz, ≤-24dB @6GHz |

#### ENVIRONMENTAL SPECIFICATIONS

|                       |                  |
|-----------------------|------------------|
| Operating Temperature | -40°C to +85°C   |
| Weather Standard      | IEC 68 40/85/ 21 |

Thank you visiting 123eWireless.

Please contact us at [sales@123ewireless.com](mailto:sales@123ewireless.com) for any queries.