



3/8in Super Flex 4.3-10 Male w/EasyBoot to NEX10 Male Low PIM Jumper
|123-38SFHMXM-XX-P-EB1 |123e.com
Part Number: 123-38SFHMXM-XX-P-EB1

4.3-10 Male with EasyBoot™ weather protection to NEX10 Male (no EasyBoot™) welded 3/8 inch Super Flexible jumper cable. The EasyBoot™ is an integrated re-enterable weather protection system MADE IN THE USA. This small cell jumper is designed with few internal components which in turn reduces the inter-modulation distortion (IMD) averaging -165dBc. Each jumper is individually certified to guarantee performance.

CROSS REFERENCE

Alternative To	SLJ38SPW-64M89M, LS2-XMHM-W-D, LS2-XMHM, LS2-XMHM-80-W1-D
----------------	---

PHYSICAL SPECIFICATIONS

Connector A	4.3-10 Male with EasyBoot
Connector B	NEX10 Male
Inner Conductor	Copper-Clad Aluminum 1.90mm (0.075in)
Outer Conductor	Helically Corrugated Copper 6.40mm (0.252in)
Jacket Color	Black
Insulation	Physically Foamed PE 4.70mm (0.185in)
Jacket Material	PE - UV Resistant
Maximum Bending Radius	2.00"

ELECTRICAL SPECIFICATIONS

Frequency Range	Max 10.2 GHz
Impedance	50±2 Ohm
Peak Power	13.2 kW
PIM	-165 dBc IEC 62037
Return Loss	-30 db

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-55°C to +85°C
Weather Standard	IEC 68 40/85/ 21

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.