

**RF 240, 1.0/2.3 Male RA to N male | 123-141023MRNM-XX | 123e.com**  
Part Number: 123-141023MRNM



1.0/2.3 Male Right Angle to N Male low loss 240 LMR240 style cable UL Riser rated indoor/outdoor with low insertion loss and return loss certification

**CROSS REFERENCE**

|                |                 |
|----------------|-----------------|
| Alternative To | LMR240, CNT-240 |
|----------------|-----------------|

**PHYSICAL SPECIFICATIONS**

|                 |                                |
|-----------------|--------------------------------|
| Connector A     | 1.0/2.3 Male Right Angle       |
| Connector B     | N Male                         |
| Coax Cable Type | Low Loss 240                   |
| Outer Diameter  | 0.24 (in)                      |
| Jacket Color    | Black                          |
| Jacket Material | PE - UV Resistant, Riser Rated |

**ELECTRICAL SPECIFICATIONS**

|                 |                               |
|-----------------|-------------------------------|
| Attenuation     | 7.0 dB/100ft @ 900 MHz =(Nom) |
| Frequency Range | 698-2200 MHz                  |
| Impedance       | 50 Ohm                        |
| Insertion Loss  | ≤-1.29 dB                     |
| Return Loss     | ≤-24 dB                       |

**ENVIRONMENTAL SPECIFICATIONS**

|                       |                |
|-----------------------|----------------|
| Operating Temperature | -40°C To +85°C |
| Weather Standard      | IP 67          |

Thank you visiting 123eWireless.

Please contact us at [sales@123ewireless.com](mailto:sales@123ewireless.com) for any queries.