



1/4" Super Flex 7/16" Male to 7/16" Male Right Angle Low PIM jumper | 123-14SFDMDMR
|123e.com

Part Number: 123-14SFDMDMR-XX-P

1/4" Super Flex 7/16" Male to 7/16" Male Right Angle welded onto 1/4 inch Super Flexible jumper cable MADE IN THE USA. This small cell or DAS jumper is designed with few internal components which in turn reduces the inter-modulation distortion (IMD) averaging -165dBc. Each jumper is individually tested and certified to guarantee performance.

CROSS REFERENCE

Alternative To	F1A-DMHM, F1A-DMDMR-20-P
----------------	--------------------------

PHYSICAL SPECIFICATIONS

Connector A	7/16" DIN Male
Connector B	7/16" DIN Male Right Angle
Outer Diameter	0.252in
Jacket Color	Black
Jacket Material	PE - UV Resistant
Maximum Bending Radius	0.78"

ELECTRICAL SPECIFICATIONS

Frequency Range	600-3000 Mhz
Impedance	50 Ohm
PIM	-168 dBc
Return Loss	≤-27dB @3GHz, ≤-24dB @6GHz

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-40°C to +85°C
Weather Standard	IEC 68 40/85/ 21

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.