

**3/8" Super Flex 4.1/9.5 Mini Din Male to 4.1/9.5 Mini Din Male Low PIM Jumper**
|123-38SFMDMMDM |123e.com
Part Number: 123-38SFMDMMDM-XX-P

4.1/9.5 Mini Din Male to 4.1/9.5 Mini Din Male welded onto 3/8" Super Flex cable, Low PIM factory made jumper. 123eWireless factory made assemblies are optimized to produce low passive third order inter-modulation. Each jumper is dynamically PIM tested to IEC 62037 standards, certified to guarantee performance, and averages -165dBc. MADE in the USA.

CROSS REFERENCE

Alternative To	F2A-KMKM-3M
----------------	-------------

PHYSICAL SPECIFICATIONS

Connector A	4.1/9.5 Mini Din Male
Connector B	4.1/9.5 Mini Din Male
Inner Conductor	Copper-Clad Aluminum 1.90mm (0.075in)
Outer Conductor	Helically Corrugated Copper 6.40mm (0.252in)
Jacket Color	Black
Insulation	Physically Foamed PE 4.70mm (0.185in)
Jacket Material	PE - UV Resistant
Maximum Bending Radius	2.00"

ELECTRICAL SPECIFICATIONS

Frequency Range	Max 10.2 GHz
Impedance	50±2 Ohm
Peak Power	13.2 kW
PIM	-165 dBc IEC 62037
Return Loss	-30 db

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-55°C to +85°C
Weather Standard	IEC 68 40/85/ 21

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.