

**2.2-5 Male to SMA Male Low Loss Fire Rated 240 | 123-14JMSMA-XX-FR | 123e.com**  
Part Number: 123-14JMSMA-XX-FR



2.2-5 Male to SMA Male LMR type low loss 240 with a fire rated jacket. This high-performance RF coaxial cable assembly is engineered for reliable, low-loss signal transmission in demanding applications. It features a fire-retardant outer jacket that meets stringent safety standards, making it ideal for environments where fire protection is critical. Designed with excellent flexibility and enhanced durability, this assembly delivers long-term performance and dependable operation in challenging installations.

**CROSS REFERENCE**

Alternative To

**PHYSICAL SPECIFICATIONS**

|                 |                          |
|-----------------|--------------------------|
| Connector A     | 2.2-5 Male               |
| Connector B     | SMA Male                 |
| Coax Cable Type | Low Loss 240, Fire Rated |
| Outer Diameter  | 6.10 ± 0.10 mm           |
| Jacket Color    | Black                    |
| Jacket Material | LSZH-FRPE                |

**ELECTRICAL SPECIFICATIONS**

|                 |                               |
|-----------------|-------------------------------|
| Frequency Range | Cut Off frequency = 31.00 GHz |
| Impedance       | 50 Ohm                        |
| Return Loss     | -18db                         |

**ENVIRONMENTAL SPECIFICATIONS**

|                       |                |
|-----------------------|----------------|
| Operating Temperature | -40°C To +85°C |
|-----------------------|----------------|

Thank you visiting 123eWireless.

Please contact us at [sales@123ewireless.com](mailto:sales@123ewireless.com) for any queries.