



1/2" Flexible 4.3-10 Male with EasyBoot to 4.3-10 Male Right Angle Low PIM Jumper
|123-1HMHMR-XX-P-EB1 |123e.com
Part Number: 123-1HMHMR-XX-P-EB1

4.3-10 Male with EasyBoot weatherproofing boot to 4.3-10 Male Right Angle welded onto 1/2" flexible cable, Low PIM factory made jumper. 123eWireless factory made assemblies are optimized to produce low passive third order inter-modulation. Each jumper is dynamically PIM tested to IEC 62037 standards, certified to guarantee performance, and averages -165dBc. MADE in the USA.

CROSS REFERENCE

Alternative To	L4-HMHR-8-SGW-D L4-HMHR-10-SGW-D L4-HMHR-12-SGW-D L4-HMHR-15-SGW-D
----------------	--

PHYSICAL SPECIFICATIONS

Connector A	4.3-10 Male with EasyBoot
Connector B	4.3-10 Male Right Angle
Outer Diameter	.63in
Jacket Color	Black
Jacket Material	PE - UV Resistant
Maximum Bending Radius	2.00"

ELECTRICAL SPECIFICATIONS

Frequency Range	600-3000 Mhz
Impedance	50 Ohm
PIM	-165 dBc IEC 62037
Return Loss	-30 db

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-40°C to +85°C
Weather Standard	IEC 68 40/85/ 21

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.