

**1/2" Flexible 4.3-10 Male to NEX10 Male Low PIM jumper | 123-1HMXM-XX-P | 123e.com**  
Part Number: 123-1HMXM-XX-P



4.3-10 Male to Nex10 Male welded onto 1/2 inch Flexible Rated Coaxial Cable. This jumper cable is MADE IN THE USA. This small cell or DAS jumper is designed with few internal components which in turn reduces the inter-modulation distortion (IMD) averaging -165dBc. Each jumper is individually tested and certified to guarantee performance.

#### CROSS REFERENCE

Alternative To

#### PHYSICAL SPECIFICATIONS

|                        |                           |
|------------------------|---------------------------|
| Connector A            | 4.3-10 Male               |
| Connector B            | NEX10 Male                |
| Outer Diameter         | 0.307in (7.8mm)           |
| Inner Conductor        | Copper clad aluminum wire |
| Outer Conductor        | Helical corrugated copper |
| Jacket Color           | Black                     |
| Insulation             | PE Spline                 |
| Jacket Material        | PE - UV Resistant         |
| Maximum Bending Radius | 1.18"                     |

#### ELECTRICAL SPECIFICATIONS

|                 |                            |
|-----------------|----------------------------|
| Frequency Range | 600-3000 Mhz               |
| Impedance       | 50±2 Ohm                   |
| PIM             | -156dBc                    |
| Return Loss     | ≤-30dB @3GHz, ≤-24dB @6GHz |

#### ENVIRONMENTAL SPECIFICATIONS

|                       |                  |
|-----------------------|------------------|
| Operating Temperature | -20°C to +80°C   |
| Weather Standard      | IEC 68 40/85/ 21 |

Thank you visiting 123eWireless.

Please contact us at [sales@123ewireless.com](mailto:sales@123ewireless.com) for any queries.