123eWireless
30412 Esperanza, Rancho Santa Margarita
CA 92688, (888) 263-6000
sales@123ewireless.com

1/4" Super Flex 4.3-10 Male to SMA Male Low PIM jumper | 123-14SFHMSMA| 123e.com
Part Number: 123-14SFHMSMA-XX-P

4.3-10 Male to SMA Male welded onto 1/4 inch Super Flexible jumper cable MADE IN THE USA. This small cell or DAS jumper is designed with few internal components which in turn reduces the inter-modulation distortion (IMD) averaging -165dBc. Each jumper is individually tested and certified to guarantee performance.

CROSS REFERENCE	
Alternative To	
PHYSICAL SPECIFICATIONS	
Connector A	4.3-10 Male
Connector B	SMA Male
Outer Diameter	0.252in
Jacket Color	Black
Jacket Material	PE - UV Resistant
Maximum Bending Radius	0.78"
ELECTRICAL SPECIFICATIONS	
Frequency Range	600-3000 Mhz
Impedance	50 Ohm
PIM	-178 dBc
Return Loss	≤-27dB @3GHz, ≤-24dB @6GHz
ENVIRONMENTAL SPECIFICATIONS	
Operating Temperature	-40°C to +85°C
Weather Standard	IEC 68 40/85/ 21

Thank you visiting 123eWireless.
Please contact us at sales@123ewireless.com for any queries.