



1/2in Flexible Riser 4.3-10 Male to 4.3-10 Male Low PIM Jumper |123-1RHHMH |123e.com
Part Number: 123-1RHHMH-XX-P

4.3-10 Male to 4.3-10 Male welded onto 1/2" flexible Riser cable, Low PIM factory made jumper. 123eWireless factory made assemblies are optimized to produce low passive third order inter-modulation. Each jumper is dynamically PIM tested to IEC 62037 standards, certified to guarantee performance and averages -165dBc. MADE in the USA.

CROSS REFERENCE

Alternative To	LDF4RK-50A
----------------	------------

PHYSICAL SPECIFICATIONS

Connector A	4.3-10 Male
Connector B	4.3-10 Male
Outer Diameter	1/2in (0.618")
Jacket Color	Black
Jacket Material	Fire retardant PE (UL 1666 for CMR CATV)
Maximum Bending Radius	2.75 inches (single)

ELECTRICAL SPECIFICATIONS

Frequency Range	600-3000 Mhz
Impedance	50 Ohm
PIM	-165 dBc IEC 62037

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-40°C to +85°C
Weather Standard	IEC 68 40/85/ 21

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.