**123eWireless**
30412 Esperanza, Rancho Santa Margarita
CA 92688, (888) 263-6000
sales@123ewireless.com

**Din (7/16) Female to 4.1-9.5 Female RF adapter | 123-DFMDF-P | 123e.com**
Part Number: 123-DFMDF-P

Din (7/16) Female to 4.1-9.5 female RF adapters are used to either change the gender from one connector type to another, to mate different connector types together, or as disposable interfaces for test and measurement applications where main launch cables need protection from wear and tear. 123eWireless RF adapters are designed for low loss with maximum mating cycles without degradation.

| | |
|---|---|
| **CROSS REFERENCE** | |
| Alternative To | SM8210, C8285 |
| **PHYSICAL SPECIFICATIONS** | |
| Mating Cycles | 500 |
| Connector A | 7/16 DIN Female |
| Connector B | 4.1-9.5 DIN Female |
| Insulation | PTFE |
| **ELECTRICAL SPECIFICATIONS** | |
| Frequency Range | DC-3GHz |
| Impedance | 50 ohm |
| Insertion Loss | ≤ 0.1 dB |
| PIM | ≤160dBc |
| VSWR | ≤1.10 @3GHz |
| **ENVIRONMENTAL SPECIFICATIONS** | |
| Weather Standard | IEC 6855 / 155/ 56 |

Thank you visiting 123eWireless.
Please contact us at sales@123ewireless.com for any queries.