123eWireless
30412 Esperanza, Rancho Santa Margarita
CA 92688, (888) 263-6000
sales@123ewireless.com

LC/UPC-LC/UPC 2F Duplex, Single Mode I/O Jumper | 123-F1D2-1A477 | 123e.com
Part Number: 123-F1D2-1A477

LC/UPC to LC UPC duplex, Singlemode 2 fiber round distribution indoor/outdoor jumper. Designed for Ericsson base station functionality for typical interconnection between RRU and BBU. CPRI, LTE and 5G ready.

CROSS REFERENCE	
Alternative To	RPM2533512
PHYSICAL SPECIFICATIONS	
Connector A	LC/UPC Duplex
Connector B	LC/UPC Duplex
Fiber Count	2
Breakout Length Side A	90mm
Breakout Length Side B	90mm
Furcation	2 mm
Outer Diameter	5.4mm
Fiber Type	SMF-28® Ultra
Jacket Color	Black
Jacket Material	OFNR, I/O
ATTENUATION	
Attenuation @ 1550nm	0.25 dB/km
Attenuation @ 1310nm	0.40 dB/km
OPTICAL SPECIFICATIONS	
Insertion Loss	< 0.5 dB
Return Loss	>50 dB
ENVIRONMENTAL SPECIFICATIONS	
Operating Temperature	-20°C to +70°C
Varmint Rating	None

Thank you visiting 123eWireless.
Please contact us at sales@123ewireless.com for any queries.