



Ruggedized LC/UPC Uniboot w/ strain relief to Optitap (SC/APC) SM Duplex 2-Fiber Round Assembly | 123-F1D2-1A4DH-XX-OM-001 | 123e.com

Part Number: 123-F1D2-1A4DH-XX-OM-001

Ruggedized LC/UPC Uniboot with strain relief to Optitap (SC/APC) SM Duplex 2-Fiber Round Assembly.

CROSS REFERENCE

Alternative To	FHBDW-H2M22-0250F
----------------	-------------------

PHYSICAL SPECIFICATIONS

Connector A	LC/UPC Uniboot with ruggedized overmold
Connector B	Duplex Optitap (SC/APC)
Fiber Count	2
Breakout Length Side A	N/A
Breakout Length Side B	2 FT
Furcation	2 mm
Outer Diameter	5.4mm
Fiber Type	SMF-28® Ultra
Jacket Color	Black
Jacket Material	OFNR, I/O

ATTENUATION

Attenuation @ 1550nm	0.25 dB/km
Attenuation @ 1310nm	0.40 dB/km

OPTICAL SPECIFICATIONS

Insertion Loss	< 0.5 dB
Return Loss	>50 dB

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-20°C to +70°C
Varmint Rating	None

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.