



LC/UPC to LC/UPC 12F, Single Mode Indoor Plenum with 36IN fanout and pulling sock with swivel hook | 123-F3X12-4A466-XX-PS | 123e.com

Part Number: 123-F3X12-4A466-XX-PS

LC/UPC simplex to LC/UPC simplex Single Mode 12 fiber indoor plenum assembly with 36 inch fanout on each end and a pulling sock with swivel hook for easy installation.

CROSS REFERENCE

Alternative To

PHYSICAL SPECIFICATIONS

Connector A	LC/UPC Simplex
Connector B	LC/UPC Simplex
Fiber Count	12
Breakout Length Side A	36 inch fanout
Breakout Length Side B	36 inch fanout
Furcation	2 mm
Outer Diameter	5.8mm
Fiber Type	SMF-28® Ultra
Jacket Color	Yellow
Jacket Material	Flame Retardant PVC

ATTENUATION

Attenuation @ 1550nm	0.25 dB/km
Attenuation @ 1310nm	0.40 dB/km

OPTICAL SPECIFICATIONS

Insertion Loss	< 0.5 dB
Return Loss	>50 dB

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	0°C to +70°C
-----------------------	--------------

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.