



LC/UPC to LC/UPC 2 Fiber Simplex Singlemode Indoor Plenum | 123-F1X2-4A466 | 123e.com
Part Number: 123-F1X2-4A466

LC/UPC to LC/UPC 4.4MM Bend 2 Fiber Simplex Singlemode Indoor Plenum with 2MM breakouts. Patch cords are custom made with Corning's SMF-28 Ultra optical fiber and meet or exceed GR-326 standards. Each assembly is optically tested, bagged, and serialized for traceability and quality purposes.

CROSS REFERENCE

Alternative To	020202R9120003M, SURG02LCLCRXXUX-3M
----------------	-------------------------------------

PHYSICAL SPECIFICATIONS

Connector A	LC/UPC
Connector B	LC/UPC
Fiber Count	2
Breakout Length Side A	3 Inches
Breakout Length Side B	3 Inches
Outer Diameter	4.4mm
Fiber Type	SMF-28® Ultra
Jacket Color	Yellow
Jacket Material	Indoor Plenum

ATTENUATION

Attenuation @ 1550nm	0.4 dB/km
Attenuation @ 1310nm	0.5 dB/km

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-20°C to +70°C
-----------------------	----------------

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.