



LC/UPC-ODC Female 2F Duplex, Single Mode I/O Riser with FiberSeal| 123-F1D2-1A4G7-XX-FS | 123e.com

Part Number: 123-F1D2-1A4G7-XX-FS

LC/UPC with FiberSeal to ODC Female (receptacle) 2F Duplex, Single Mode I/O Riser

CROSS REFERENCE

Alternative To 2F-SM-LCD

PHYSICAL SPECIFICATIONS

Connector A LC/UPC Duplex with FiberSeal (FullAXS type weather protection)

Connector B ODC (AARC) Female receptacle

Fiber Count 2

Breakout Length Side A 6IN

Breakout Length Side B N/A

Furcation 2 mm

Outer Diameter 5.4mm

Fiber Type SMF-28® Ultra

Jacket Color Black

Jacket Material OFNR, I/O

ATTENUATION

Attenuation @ 1550nm 0.25 dB/km

Attenuation @ 1310nm 0.40 dB/km

OPTICAL SPECIFICATIONS

Insertion Loss < 0.5 dB

Return Loss >50 dB

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature -20°C to +70°C

Varmint Rating None

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.