

**LC/UPC to LC/UPC 12F Distribution, Single Mode I/O Riser, w/pulling sock | 123-F3X12-1A466-XX-PS | 123e.com**

Part Number: 123-F3X12-1A466-XX-PS



LC/UPC to LC/UPC simplex Single Mode 12 fiber round distribution indoor/outdoor jumper with a pulling sock for easy installation.

**CROSS REFERENCE**

Alternative To

**PHYSICAL SPECIFICATIONS**

|                        |                |
|------------------------|----------------|
| Connector A            | LC/UPC Simplex |
| Connector B            | LC/UPC Simplex |
| Fiber Count            | 12             |
| Breakout Length Side A | 18 Inches      |
| Breakout Length Side B | 18 Inches      |
| Furcation              | 2 mm           |
| Outer Diameter         | 5.8mm          |
| Fiber Type             | SMF-28® Ultra  |
| Jacket Color           | Black          |
| Jacket Material        | OFNR, I/O      |

**ATTENUATION**

|                      |            |
|----------------------|------------|
| Attenuation @ 1550nm | 0.25 dB/km |
| Attenuation @ 1310nm | 0.40 dB/km |

**OPTICAL SPECIFICATIONS**

|                |          |
|----------------|----------|
| Insertion Loss | < 0.5 dB |
| Return Loss    | >50 dB   |

**ENVIRONMENTAL SPECIFICATIONS**

|                       |                |
|-----------------------|----------------|
| Operating Temperature | -20°C to +70°C |
| Varmint Rating        | None           |

Thank you visiting 123eWireless.

Please contact us at [sales@123ewireless.com](mailto:sales@123ewireless.com) for any queries.