



ODC TO DLC/SFP, SM, 2F Round Distribution Armored | 123-F4D2-1A4G7-XX-OSFP | 123e.com

Part Number: 123-F4D2-1A4G7-XX-OSFP

Remote Radio Head (RRH) ODC Receptacle (female) to LC/UPC Duplex with OCTIS/SFP Singlemode, 2F Round Distribution Armored Assembly. This assembly includes the Octis Plug Kit SFP OCTI117500 from Radiall.

CROSS REFERENCE

Alternative To	FOJBF-OSFP01S-xxM
----------------	-------------------

PHYSICAL SPECIFICATIONS

Connector A	ODC (RFX) female receptacle
Connector B	LC/UPC Duplex with Octis/SFP
Fiber Count	2
Breakout Length Side A	N/A
Breakout Length Side B	3in
Outer Diameter	5.0mm
Fiber Type	G652D MM62.5/125 G657
Jacket Color	Black
Aarmor	Kevlar over 2.0mm±0.05 Stainless steel tube diameter
Bend Radius Single	50mm 100mm dynamic
Jacket Material	LSZH Indoor/Outdoor,

ATTENUATION

Attenuation @ 1550nm	0.25 dB/km
Attenuation @ 1310nm	0.40 dB/km

ELECTRICAL SPECIFICATIONS

Return Loss	>50 dB
-------------	--------

OPTICAL SPECIFICATIONS

Insertion Loss	< 0.5 dB
Return Loss	>50 dB

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-25C to +85C
-----------------------	--------------

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.