

**N Male to N Female 30dB 2 Watts Attenuator | 123-N30DB2W | 123e.com**  
Part Number: 123-N30DB2W



N (M) to N (F) 30 dB 2 Watts Attenuator. Fixed attenuators are used to lower voltage, dissipate power, and to improve impedance matching.

- Wide Frequency Band DC-6GHz
- 2G/3G/4G/LTE Coverage
- Low VSWR
- Widely used for In-building Solutions

## CROSS REFERENCE

Alternative To

## PHYSICAL SPECIFICATIONS

|             |          |
|-------------|----------|
| Connector A | N Male   |
| Connector B | N Female |

## ELECTRICAL SPECIFICATIONS

|                 |                |
|-----------------|----------------|
| Attenuation     | 30dB $\pm$ 1.5 |
| Average Power   | 2 W            |
| Frequency Range | DC-6GHz        |
| Impedance       | 50 ohm         |
| VSWR            | $\leq$ 1.25    |

## ENVIRONMENTAL SPECIFICATIONS

|                       |            |
|-----------------------|------------|
| Operating Temperature | -30C ~+65C |
|-----------------------|------------|

Thank you visiting 123eWireless.

Please contact us at [sales@123ewireless.com](mailto:sales@123ewireless.com) for any queries.