

**NEX10 Male 5 Watt RF Load Terminator | 123-XMT5 | 123e.com**
Part Number: 123-XMT5

The NEX10 Male 5 Watt RF Load Terminator (123-XMT5) is designed to safely terminate radio frequency signals in communication systems. It features a NEX10 male connector, operates across a DC to 6 GHz frequency range, and handles up to 5 watts of average power. With an impedance of 50 ohms and a VSWR of ≤ 1.15 , it ensures minimal signal reflection. The terminator is built to withstand operating temperatures from -22°F to 149°F and meets IEC 60068 40/085/21 and IP67 weather standards, making it suitable for various environmental conditions.

CROSS REFERENCE

Alternative To	TK-205BMT, TK-605BMT
----------------	----------------------

PHYSICAL SPECIFICATIONS

Weight	0.057 lbs
Connector A	Nex10
Gender	Male

ELECTRICAL SPECIFICATIONS

Average Power	5 Watts
Frequency Range	DC-6Ghz
Impedance	50 ohm
VSWR	≤ 1.15

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-22 to 149F
Weather Standard	IEC 60068 40 / 085/ 21; IP67

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.