123eWireless
30412 Esperanza, Rancho Santa Margarita
CA 92688, (888) 263-6000
sales@123ewireless.com

Din (7/16) Female to 4.1-9.5 Female RF adapter | 123-DFMDF-P | 123e.com
Part Number: 123-DFMDF-P

Din (7/16) Female to 4.1-9.5 female RF adapters are used to either change the gender from one connector type to another, to mate different connector types together, or as disposable interfaces for test and measurement applications where main launch cables need protection from wear and tear. 123eWireless RF adapters are designed for low loss with maximum mating cycles without degradation.

CROSS REFERENCE	
Alternative To	SM8210, C8285
PHYSICAL SPECIFICATIONS	
Mating Cycles	500
Connector A	7/16 DIN Female
Connector B	4.1-9.5 DIN Female
Insulation	PTFE
ELECTRICAL SPECIFICATIONS	
Frequency Range	DC-3GHz
Impedance	50 ohm
Insertion Loss	≤ 0.1 dB
PIM	≤160dBc
VSWR	≤1.10 @3GHz
ENVIRONMENTAL SPECIFICATIONS	
Weather Standard	IEC 6855 / 155/ 56

Thank you visiting 123eWireless.
Please contact us at sales@123ewireless.com for any queries.