

4.3-10F 2 Way Wide Band Power Splitter | 123-SPHF2300W | 123e.com

Part Number: 123-SPHF2300W



2-Way Power Splitter

Model 123-SPHF2300W · Reactive type · IP67

Engineered for demanding wireless infrastructure deployments, the splitter is a wideband 2-way reactive power splitter covering 600–6000 MHz. With support for Tetra, 2G, 3G, 4G/LTE, and 5G signals in a single unit, it is an ideal choice for in-building distributed antenna systems (DAS) and outdoor base station installations.

PHYSICAL SPECIFICATIONS

Connector A	4.3-10 Female
-------------	---------------

ELECTRICAL SPECIFICATIONS

Frequency Range	600-6000MHz
Impedance	50 ohm
Insertion Loss	≤ 0.2 (600-2700MHz) ≤ 0.3 (2700-6000MHz)
PIM	≤ -16 dBc@2*43dBm (698-2700)
Split Loss	3.0dB
Total Input Power	300W
VSWR	≤ 1.3

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-35C~+75C
Weather Standard	Indoor or Outdoor, IP67

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.